



Model		LT65ADP	
Product picture	 		
Display specification			
Diagonal display size			65(inch)
Bezel color	Aluminum frame(Black color)		√
Panel type	Ultra HD Direct type LED		√
Active area (mm)			1428.48 (H) * 803.52 (V)
Resolution	3840*2160 /60hz		√
Pixel Pitch			0.372mm x 0.372mm
Hardness Glass	Mohs-7 level with 4mm Temp*		√
Glass Panel	Anti-Glare glass with zero bonding		√
Aspect Ratio	16:9		√
Contrast Ratio	1200:1 (type)		√
Dvnamic Contrast Ratio	5000:1		√
Brightness	400cd/m2		√
Color depth	1.07 billion colors		√
Viewing angle	178°		√
Lifespan	60,000 hours		√
Touch Type			
Touch Technology	IR touch		√
Multi Touch	Max 40 points(Windows)		√
Multi Writing	Max 20 points(Windows)		√
Touch Precision	1 mm (over 90% Area)		√
Auto-Calibration	Yes		√
Anti-light	Yes		√
Minimum object size	2mm		√
Touch Response Time	First Point <2 ms, Continuation <8 ms		√
Supporting OS	Windows 7/8/10/11; Android; Mac; Linux; Chrome OS		√
Sound			
Front Speakers	15W*2		√
Total Power Amplifiers	≤60w		√
Front Side Connections			
Front Ports	USB3.0 * 3 lines (Public for both Android & PC) ; Touch out USB B type * 1 line; HDMI in 2.0 * 1 line ; USB-C * 1 line		
Front Keys	Power on/off; Signal source; Return; Main page; Menu; Volume down; Volume up		
Bottom Side Connections			
TF Card	1		√
Audio	In* 1, Out *1		√
Public USB-A 3.0	1		√
OTG USB-A 2.0	1		√
LAN-Port IN	1 (RJ45, 100 Mbit/s)		√
LAN-Port OUT(option)	1 (RJ45, 100 Mbit/s)		√
SPDIF	1		√
RS232(option)	1 x DB9 Male		√
HDMI IN	1		√
USB-B (touch)	1		√
HDMI OUT	1		√
Windows OPS Slot	80-pins OPS slot		√
WiFi Standard	Wi-Fi 5(2.4G+5G)		√
Bluetooth version	5.0		√
Riotouch Central			
Android Version	Android 14		√
Chip	GK6780v100		√
CPU	High-End (8 Cores-A55) 1.2GHz		√
GPU	High-End (Mali-G52 MP2(2EE))		√
Memory	8GB DDR4		√
Storage	128GB		√
Compliant with	Windows; Mac; Linux; Chrome OS		√
Over-the-Air Updates (OTA)	YES		√
OPS Standard			
Model	U3133 : 80 PIN		
CPU	13Gen Intel® CoRE™ i3-1315U/Processor		
RAM	8GB DDR4 2666 8G Memory		
ROM	128GB *M.2 NVMe		
Graphics	Intel® UHD Graphics for 13th Gen Intel® Processors		
Graphics output	HDMI/DP Support synchronous and asynchronous dual display		
Ethernet	LAN : 1* 8111H 10M/100M/1000M Ethernet		
	WiFi : 1*M.2 2230 for Wifi6+BT 5.0		
Audio	Cmedia USB Audio (HS100B)		
I/O			
Front	1*HDMI2.0 out 1*DP1.4 out 5*USB 3.0 1*USB2.0 1* RJ45 1*Power 1* Restore		
	1*Sound_out 1*Sound_in 1*Type-C(USB 2.0) 1*Power LED 1*HDD/SSD LED 2*WIFI/BT ANT		
Interface			
Rear	1*JAE 80PIN ; HDMI2.0 out(4K/60Hz)		
Power			
Power	19V4.74A		
Size			
SIZE (mm)	Product : 195*180*42mm Packing : 282*258*77mm		
Weight (kg)	N.W.≈1.2 Kg G.W ≈1.4Kg		
Environment			
Operating Temp.	0°C~ 45°C		
Storage Temp.	-40°C- 80°C		
Operating Humidity	10% - 95% @40°C non-condensable		
System			
Operation system	Windows 11		
Office software	Microsoft office 2021*		
General Information			
Power Supply	~ 100-260 V (50/60Hz)		√
Switch On / Off	Yes		√
Standby Energy Consumption	≤ 0.5 Watt		√
Power Consumption			Maximun< 290W Eco<75W
Net Weight	(KG±2)		40
Gross Weight	(KG±2)		50
Screen Dimensions	(WxDxH)		1470.9 *97.5* 897.5 mm
Dimensions Package	(WxDxH)		1622 * 222 * 1044 mm
VESA Standard	(mm)		600*400 mm
Certifications	CE: EMC + LVD / RoHS / REACH / FCC/CCC		√
Warranty	THREE years		√

Environmental conditions		
Operating Temperature	0°C - 38°C/32 - 100 °F	√
Storage Temperature	-20°C - 60°C/-4 - 140 °F	√
Storage Humidity	10 % - 90 %	√
Usage Humidity	10 % - 90 %	√
Accessories		
Accessories	No ink pen * 2pcs, Remote control *1pc, 1.5m power cord *1pc, 1.5m HDMI cable *1pc, 1.5m USB touch cable *1pc; wall mount kit	