Dong Guan RioTouch Technology Co., Ltd

Floor 5, Building 1, Huihang High-Tech Industrial Park, No. 9 Zhongnan Road, Shangsha, Chang'an Town, Dongguan City, Guangdong Province, China

Web: www.RioTouch.com

Poster LED

Model		KI 92	KI 80
Product Images			
Display specification			
Diagonal display size (inch)		92(inch)	80(inch)
Bezel color	Aluminum Frame White (Black Optional)	√	√
Panel type		GOB	COB
Active area (WxH, mm)	mm	1280*1920	640*1920
Resolution (WxH, px)		688*1032	512*1536
Pixel Pitch		GOB P1.86	COB P1.25
Module size (WxH, mm)	mm	320*160	320*160
Contrast Ratio	5000:1	√	√
Brightness	600 cd/m2	√	√
Refresh Rate	3840 Hz	√	√
Viewing angle	160° (H) / 160° (V)	√	√
Lifespan	50,000 hours	√	√
Viewable Area (m2)		2.4576	1.2288
Brightness Uniformity	≥98%	√	√
Color Temperature (K)	5000~10000 K	√	√
Folding type		Up/Down folding or Left/Right folding	Up/Down folding
Sound			
Speaker	2	√	√
Speaker Power	5W*2	√	√
Speaker Total Power	≤10 W	√	√
Ports / Interfaces			
HDMI IN	1	√	√
USB2.0	2	√	√
RJ45	1	√	√
Mainboard parameters			
Chipset	H618	√	√
Android version	12	√	√
CPU	Cortex-A53	√	√
GPU	G31 MP2	√	√
DDR	4GB	√	√
EMMC	32GB (64GB for option)	√	√
WiFi	6 (802.11ax)	√	√
BT	5.0	√	√

Remote upgrade	Yes	√	√
Power-on Indicator			
Auto power-on		√	√
Overall parameters			
Power Supply	AC 100-240 V, 50/60 Hz	√	√
Standby Energy Consumption	≤ 0.5 Watt	√	√
Power Consumption	W	≤610W	≤330W
Machine Dimensions (mm)	(WxDxH)	1280*60*2070	660*65*2100
Dimensions Package	(WxDxH)		
Environmental conditions			
Operating Temperature	0°C - 38°C / 32 - 100°F	√	√
Storage Temperature	-20°C - 60°C / -4 - 140°F	√	√
Usage Humidity	10 % - 90 %	√	√
Storage Humidity	10 % - 90 %	√	√
Accessories			
Accessories	Power cord (5 m) ×1, Antenna rod ×1		