


Indoor Curved LED Product Display Stand

320x960mm*4

P1.25 / P1.538 / P1.86 / P2 / P2.5



Curved four-sided display

650 cd/m² indoor

GOB protected

Transparent top showcase

Lockable casters

APP & cloud content control

Key Features

- Curved four-sided display** — 320 × 960 mm × 4 curved sides, 1.2288 m² display area.
- Indoor brightness 650 cd/m²** — 3840 Hz / 7680 Hz refresh, flicker-free on camera.
- Mobile APP & cloud content control** — update posters and videos from a phone, no PC needed.
- Low running cost** — 147 W average; 492 W max, 28.5 kg total weight.
- Ultra HD, GOB protected** — P1.25 – P2.5 pitch; GOB coated, waterproof & anti-collision.
- Transparent top showcase** — put the actual product on top for 360° visibility.
- Lockable casters** — one person can reposition and lock the stand.
- Front maintenance** — magnetic module adsorption for fast front-side service.

Where It Works — Retail, F&B, Healthcare & Campus



Retail & Brand Stores



Restaurants & Cafés



Hospitals, Pharmacies & Campuses

Technical Specifications

Item	Specification
Model	P1.25 / P1.538 / P1.86 / P2 / P2.5
Pixel Pitch	P1.25 mm / P1.538 mm / P1.86 mm / P2 mm / P2.5 mm
Module Size	320 × 160 mm
Module Resolution	256 × 128 / 208 × 104 / 172 × 86 / 160 × 80 / 128 × 64 dot
Lamp Bead / Craft	1010+GOB / 1212+GOB / 1515+GOB — GOB coated, waterproof & anti-collision
Scan Mode	64S / 52S / 43S / 40S / 32S
Number of Modules	1 × 6 × 4
Display Size	320 × 960 mm × 4 curved sides
Display Area	1.2288 m ²
Full Screen Resolution	256 × 768 × 4 / 208 × 624 × 4 / 172 × 516 × 4 / 160 × 480 × 4 / 128 × 384 × 4
Brightness	650 cd/m ² (indoor)
Refresh Frequency	3840 Hz / 7680 Hz
Gray Level	14–16 bit
Maintenance Method	Magnetic adsorption, front maintenance
Average Power Consumption	147 W
Max Power Consumption	492 W
Whole Screen Weight	28.5 kg
Top Showcase	Transparent showcase for product display (360° visibility)
Mobility / Installation	Lockable casters, single-person repositioning
Content Control	Mobile APP & cloud content upload, plug & play
Content Features	Naked-eye 3D content support

Notes: Specifications are subject to change without notice. Product images are for illustration purposes only. Values refer to the standard curved four-sided 320 × 960 mm configuration; the unit is supplied with a transparent top showcase and lockable casters.

Options & Customisation

- Pixel pitch selection: P1.25 – P2.5
- APP / cloud content control setup
- Module layout 1 × 6 × 4 (320 × 160 mm)
- OEM / ODM enquiries welcome