



Rio Touch Technology Co., Ltd

5th Floor, Huihang High-tech Industrial Park, No. 9 Zhongnan Middle Road, Chang'an Town, Dongguan City, Guangdong Province

Website: www.RioTouch.com

Seat-mounted advertising machine

Model		U+32	U+43
Product Images			
Display Specifications			
Screen diagonal size		32 (inch)	43 (inch)
Screen type	DLED	√	√
Screen size (mm)		697.3056 * 392.2344	941.184 * 529.416
resolution	3840*2160	√	√
Pixel pitch (mm)		0.18159 * 0.18159	0.2451 * 0.2451
Hardness of tempered glass	Mohs hardness7class	√	√
Glass type	tempered glass	√	√
Aspect Ratio	16:9	√	√
Contrast	1200:1 (type)	√	√
Screen brightness	200cd/m2	√	√
Viewing angle	89/89/89/89 (Typ.)(CR≥10)	√	√
Theoretical service life	50,000Hour	√	√
Touch specifications			
Touch technology	Capacitive touch	√	√
Multi-touch	10point	√	√
Touch accuracy	1 mm	√	√
Automatic calibration	yes	√	√
Minimum recognition point	2mm	√	√
Response time	Greater than2msLess than8ms	√	√
Speaker specifications			
speaker	2	√	√
Speaker power	5W*2	√	√
Total power	≅10w	√	√
Interface Specifications			
HDMI IN	1	√	√
VGA	1	√	√
USB 3.0	4	√	√
RJ45 IN((1000M)	1	√	√
MIC IN	1	√	√
Line-out	1	√	√
Motherboard configuration			
System version	Windows 11	√	√
chip	Intel® B250	√	√
CPU	I5 8400	√	√
Memory	16G (32G0ptionalDDR4	√	√
harddisk	256G (512G0ptional)	√	√
Bluetooth version	5.0	√	√
WIFIVersion	WiFi6	√	√

Overall parameters			
power supply voltage	~ 100-240 V (50/60Hz)	√	√
Switch	yes	√	√
standby power consumption	≤ 0.5Wats	√	√
Overall power consumption		Maximum power < 60W Eco < 25W	Maximum power < 80W Eco < 25W
Overall dimensions (mm)	Length * Width * Height	742 * 439 * 64.2	984.4 * 578.3 * 73.5
Overall packaging dimensions (mm)	long *Width * high	832 * 530 * 150	1085 * 705 * 170
Base size (mm)	Length * Width * Height	434 * 370 * 961.58	468 * 437.6 * 968.24
Base packaging dimensions (mm)	Length * Width * Height	475 * 450 * 970	510 * 475 * 1000
Warranty	The product comes with a one-year warranty. (Extension is available as an optional service.)	√	√
Environmental conditions			
Operating temperature	0°C - 38°C / 32 - 100 F	√	√
Storage temperature	-20°C to 60°C / -4°C to 140°C	√	√
Operating humidity	10% - 90%	√	√
Storage humidity	10% - 90%	√	√
appendix			
Accessories	Power cord (1.5(meters), antenna rods (2 pieces)		