

POSTER LED

Model		KI 92	KI 83
Product Images			
Display specification			
Diagonal display size		92(inch)	(inch)
Bezel color	Aluminum Frame White (Black Optional)	√	√
Panel type		GOB	COB
Active area (mm)	MM		
Resolution			
Pixel Pitch		P1.86	P1.25
Contrast Ratio	5000:1	√	√
Brightness	600cd/m2	√	√
Refresh Rate	3840HZ	√	√
Viewing angle	160° (H) / 160° (V)	√	√
Lifespan	50,000 hours	√	√
Viewable Area			
Brightness Uniformity	≥98%	√	√
Color Temperature (K)	500~10000	√	√
Sound			
Speaker	2	√	√
Speaker Power	5W*2	√	√
Total Power	≤10w	√	√
Ports / Interfaces			
USB3.0	2	√	√
Power-on Indicator			
Auto power-on		√	√
Overall parameters			
Power Supply	~ 100-240 V (50/60Hz)	√	√
Standby Energy Consumption	≤ 0.5 Watt	√	√
Power Consumption	Watt	≤210W	≤250W
Machine Dimensions (mm)	(WxDxH)		
Dimensions Package	(WxDxH)		
Warranty	The product comes with a one-year warranty. (Extension is available as an optional service.)	√	√
Environmental conditions			
Operating Temperature	0°C - 38°C / 32 - 100°F	√	√
Storage Temperature	-20°C - 60°C / -4 - 140°F	√	√
Usage Humidity	10 % - 90 %	√	√
Storage Humidity	10 % - 90 %	√	√
Accessories			
Accessories	Power cord (5 meters)		