



Dong Guan RioTouch Technology Co., Ltd

5th Floor, Huihang High-tech Industrial Park, No. 9 Zhongnan Middle Road, Chang'an Town, Dongguan City, Guangdong Province

Web: www.RioTouch.com

IR Touch Interactive Flat Panel Display

Model		LTF65RK3588	LTF75RK3588	LTF86RK3588
Product picture	 			
Display specification				
Diagonal display size		65(inch)	75(inch)	86(inch)
Bezel color	Aluminum frame(White color)	√	√	√
Panel type	Ultra HD Direct type LED	√	√	√
Active area (mm)		1428.48 (H) * 803.52 (V)	1649.66(H) * 927.93(V)	1895.04 (H) * 1065.96(V)
Resolution	3840*2160 /60hz	√	√	√
Pixel Pitch		0.372mm x 0.372mm	0.429 mm x 0.429 mm	0.4935 mm x 0.4935
Hardness Glass	Mohs-7 level	√	√	√
Glass Panel	Anti-Glare glass with zero bonding	√	√	√
Aspect Ratio	16:9	√	√	√
Contrast Ratio	1200:1 (type)	√	√	√
Brightness	350cd/m ²	√	√	√
Color depth	1.07 billion colors	√	√	√
Viewing angle	178°	√	√	√
Lifespan	50,000 hours	√	√	√
Touch Type				
Touch Technology	IR touch	√	√	√
Multi Touch	Max 40 points(Windows)	√	√	√
Multi Writing	Max 20 points(Windows)	√	√	√
Touch Precision	1 mm (over 90% Area)	√	√	√
Auto-Calibration	Yes	√	√	√
Anti-light	Yes	√	√	√
Minimum object size	2mm	√	√	√
Touch Response Time	First Point <2 ms, Continuation <8 ms	√	√	√
Supporting OS	Windows 7/8/10/11; Android; Mac; Linux; Chrome OS	√	√	√
Sound				
Front Speakers	20W*2	√	√	√
Subwoofer	20W*1	√	√	√
Total Power Amplifiers	≅ 60w	√	√	√
Microphone (option)				
Type	Wide-area microphones	√	√	√
Number of Microphones	8	√	√	√
Auto switch (Windows/Central)	Yes	√	√	√
Disconnectable	Yes	√	√	√
Camera (option)				
Number of images	4800M (AI) /6400M	√	√	√
Maximum resolution and frame rate	4208*3120(30fps)	√	√	√
FOV(field of view)	D=119° H=97° V=74°	√	√	√
Front Side Connections				
Front Ports	Type-C * 1 line; HDMI IN * 3 line; USB3.0*2; USB-B*1			
Front Keys	Power on/off; Signal source; Setting; ECO; HOME; Volume down; Volume up			
NFC	√			
Fingerprint	√			
Bottom Side Connections				
COAX	1	√	√	√
RJ45 IN	1	√	√	√
MIC IN	1	√	√	√
Earphone	1	√	√	√
RS232	1	√	√	√
Side Connection				

TOUCH OUT	1	√	√	√
HDMI 2	1	√	√	√
HDMI 1	1	√	√	√
HDMI OUT	1	√	√	√
Public USB2.0	1	√	√	√
Android USB3.0	1	√	√	√
TYPE-C out	1	√	√	√
TF CARD	1	√	√	√
WIFI	IEEE802.11a/b/g/n/ac/ax BT+WIFI	√	√	√
Windows OPS Slot	80-pins OPS slot	√	√	√
Bluetooth version	5.2	√	√	√
Riotouch Central				
Android Version	Android 15.0	√	√	√
Chip	RK3588	√	√	√
CPU	quad-core Cortex-A76 and quad-core Cortex-A55, 2.2~ 2.4GHz	√	√	√
GPU	Mali-G610 MC4	√	√	√
RAM	8G Byte , Max.32G Byte DDR	√	√	√
Flash	128G Byte, Max.512G Byte EMMC	√	√	√
Compliant with	Windows; Mac; Linux; Chrome OS	√	√	√
Over-the-Air Updates (OTA)	YES	√	√	√
Light Sensor	YES	√	√	√
NFC Reader/Writer	YES	√	√	√
Fingerprint module	YES	√	√	√
General Information				
Power Supply	100-240 V (50/60Hz)	√	√	√
Switch On / Off	Yes	√	√	√
Standby Energy Consumption	≤ 0.5 Watt	√	√	√
Power Consumption		Maximun< 290W Eco<75W	Maximun< 320W Eco<75W	Maximun< 350W Eco<75W
Net Weight	(KG±2)	45	55	70
Gross Weight	(KG±2)	55	68	85
Screen Dimensions	(WxDxH)	1485 *102*900mm	1707*102*1025 mm	1953*102*1164 mm
Dimensions Package	(WxDxH)	1594*170*1005 mm	1818*165*1120mm	2055*168*1272mm
VESA Standard	(mm)	400*500 mm	400*700 mm	600*800 mm
Certifications	CE: EMC + LVD / RoHS / FCC/CCC	√	√	√
Warranty	ONE year for the whole product and THREE years for touch parts by default. (can be extended, it's for an option)	√	√	√
Environmental conditions				
Operating Temperature	0°C - 40°C/32 - 100 °F	√	√	√
Storage Temperature	-20°C - 60°C/-4 - 140 °F	√	√	√
Storage Humidity	10 % - 90 %	√	√	√
Usage Humidity	10 % - 90 %	√	√	√
Accessories				
Accessories	WIFI antenna*3pcs; No ink pen * 2pcs, Remote control *1pcs, 1.5m power cord *1pcs, 1.5m HDMI cable *1pcs, 1.5m USB touch cable *1pcs; wall mount kit			